

# AGRIMAX V-FLECTO

|                  |                              |
|------------------|------------------------------|
| <b>TYRE SIZE</b> | <b>VF 600/70 R 28 NRO</b>    |
| <b>UM</b>        | IS STANDARD                  |
| <b>MACHINERY</b> | HIGH-POWER TRACTOR / TRACTOR |
| <b>VERSION</b>   | STANDARD                     |
| <b>TL/TT</b>     | TL                           |
| <b>LI/SS</b>     | 167 D                        |



## DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 603  | <b>RIM REC</b> | DW 21 B         |
| <b>OD (MM)</b>  | 1551 | <b>RIM ALT</b> | DW 20 B         |
| <b>SLR (MM)</b> | 662  | <b>ECE</b>     | E11-106R-008814 |
| <b>RC (MM)</b>  | 4596 | <b>SRI</b>     | 725             |

## LOAD CAPACITY (KG/TYRE)

| KM/H / BAR                            | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  |
|---------------------------------------|------|------|------|------|------|------|------|
| <b>70</b>                             | 2425 | 2820 | 3270 | 3665 | 4060 | 4455 | 4955 |
| <b>FROM 65 TO 40</b>                  | 2670 | 3105 | 3595 | 4030 | 4465 | 4905 | 5450 |
| <b>30</b>                             | 2720 | 3165 | 3665 | 4110 | 4555 | 4995 | 5555 |
| <b>20</b>                             | 2775 | 3225 | 3735 | 4190 | 4645 | 5095 | 5665 |
| <b>10</b>                             | 2935 | 3415 | 3955 | 4435 | 4915 | 5395 | 5995 |
| <b>*UPTO 10 CYC WITH FRONT LOADER</b> | 3735 | 4345 | 5035 | 5645 | 6255 | 6865 | 7630 |
| <b>10 HT</b>                          | 2720 | 3165 | 3665 | 4110 | 4555 | 4995 | 5555 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.