


FORESTMAX

| | |
|---------------------|--|
| TIRE SIZE | 600/60 R 28 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR / AUTOCARGADORA |
| VERSIÓN | STEEL BELTED |
| TIRE TYPE | TL |
| LI/SS | 152 A8 ; 149 B |



DIMENSIONES IS STANDARD

| | | | |
|-----------------|------|----------------|------------------|
| SW (MM) | 570 | RIM REC | DW18L |
| OD (MM) | 1431 | RIM ALT | DW20B |
| SLR (MM) | 655 | ECE | E11-106R-0010523 |
| RC (MM) | 4315 | SRI | 675 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.2 | 1.4 | 1.6 | 1.8 | 2.0 | 2.2 | 2.4 |
|---------------------|------|------|------|------|------|------|------|
| 50 | 2210 | 2470 | 2535 | 2795 | 3020 | 3120 | 3250 |
| 40 | 2415 | 2700 | 2770 | 3055 | 3300 | 3410 | 3550 |
| 30 | 2585 | 2890 | 2965 | 3270 | 3535 | 3650 | 3800 |
| 25 | 2685 | 3000 | 3080 | 3395 | 3670 | 3790 | 3945 |
| 20 | 2975 | 3325 | 3410 | 3760 | 4065 | 4200 | 4370 |
| 15 | 3240 | 3620 | 3715 | 4095 | 4425 | 4570 | 4760 |
| 10 | 3625 | 4050 | 4155 | 4580 | 4950 | 5115 | 5325 |
| 10 FORESTRY SERVICE | - | - | - | - | - | - | 4370 |
| 0 FORESTRY SERVICE | - | - | - | - | - | - | 8165 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.