

FLOTATION 648

TIRE SIZE	700/50 - 22.5
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ENFARDADEIRA DE FENO / CEIFEIRA / ESPALHADOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
VERSÃO	HIGH SPEED
TIRE TYPE	TL
LI/SS DRIVE WHEEL	158 B/154 E
LI/SS FREE ROLLING	170 B/166 E



DIMENSÕES US STANDARD

CÓDIGO USA	94025596	RC (IN)	148.6
SW (IN)	27.6	RIM REC	24.00
OD (IN)	50.0	ECE	E11-106R-004555
SLR (IN)	21.7	PR	16

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	29	32	35
5 FR	18580	19640	20680
10 FR	16720	17680	18610
20 FR	14860	15720	16540
25 FR	13270	14030	14770
30 FR	11950	12630	13230
45 FR	10480	11090	11680
5 DW	13180	13930	14660
10 DW	11860	12540	13190
20 DW	10540	11140	11730
25 DW	9410	9950	10470
30 DW	8480	8960	9370
45 DW	7440	7860	8270

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.