


# AGRIMAX RT 765

<b>TYRE SIZE</b>	<b>320/70 R 24</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	116 D



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94063031	<b>RC (IN)</b>	127.8
<b>SW (IN)</b>	12.6	<b>RIM REC</b>	W 10
<b>OD (IN)</b>	43.1	<b>RIM ALT</b>	W 9; W 11
<b>SLR (IN)</b>	19.8	<b>ECE</b>	E11-106R-005827

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23
40	1520	1760	2020	2260	2510	2760
30	1600	1860	2120	2380	2650	2900
25	1660	1940	2220	2480	2760	3020
20	1750	2040	2330	2610	2900	3170
5 LT	2040	2370	2700	3030	3360	3690
5 HT	1750	2040	2330	2610	2900	3170

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.