


# EARTHMAX SR 49 M

<b>TIRE SIZE</b>	<b>26.5 R 25</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	БУЛЬДОЗЕР / ПОГРУЗОЧНО-ДОСТАВОЧНАЯ МАШИНА / ПОГРУЗЧИК / НИЗКОПРОФИЛЬНЫЙ САМОСВАЛ
<b>VERSION</b>	CUT RESISTANT COMPOUND
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	193 B ; 202 A2



## РАЗМЕРЫ IS STANDARD

<b>OD (MM)</b>	1782	<b>TRA CODE</b>	E4/L4
<b>SLR (MM)</b>	801	<b>STAR RATING</b>	★★/★
<b>RC (MM)</b>	5297		
<b>RIM REC</b>	22.00/3.0		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	4.00	4.25	4.50	4.75	5.00	5.25
50	9500	9750	10300	10600	11200	11500
10	12850	13200	14000	14500	15000	-

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.