



IS standard



GROWING TOGETHER

TR 171



PRODUCT DATA SHEET



Bias



Technologies



Special Compound



Extra Deep Tread

Performance



Traction



High Load Capacity



Self-Cleaning



Durability



TR 171

TR 171 is a deep tread tire suitable for tractors in soil tillage operations. Thanks to its outstanding self-cleaning properties, it is ideal for wet and moist soil. Designed with a special compound, TR 171 provides excellent traction and extraordinary durability also in the harshest operating conditions.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 12"	5.00 - 12	3.00 D DT ; 3.00 D	4 JA ; 3.50 B	130	580	272	1750	STD	4	TT	61 A6
	5.00 - 12	3.00 D DT ; 3.00 D	4 JA ; 3.50 B	130	580	272	1750	STD	6	TT	67 A6
	6.00 - 12	4.00 E DT ; 4.00 E	4 JA	160	635	298	1953	STD	6	TT	76 A6
Ø 16"	9.5 - 16	W 8 L	8 LB	241	845	395	2607	STD	6	TT	96 A6
Ø 18"	8.00 - 18	W 6	W 7 ; 5.50 F	190	845	391	2617	STD	4	TT	85 A6
	8.00 - 18	W 6	W 7 ; 5.50 F	190	845	391	2579	STD	6	TT	94 A6
	8.00 - 18	W 6	W 7 ; 5.50 F	190	845	391	2617	STD	8	TT	100 A6
	9.5 - 18	W 8	-	241	900	423	2790	STD	8	TT	105 A6
Ø 20"	8.3 - 20	W 7	W 6	210	900	423	2704	STD	6	TT	96 A6
	8.3 - 20	W 7	W 6	210	900	422	2788	HD	6	TT	96 A6
	8.3 - 20	W 7	W 6	210	900	422	2806	STD	8	TT	101 A6
	8.3 - 20	W 7	W 6	210	900	424	2785	HD	8	TT	101 A6
	9.5 - 20	W 8	W 7	241	955	449	2942	STD	6	TT	101 A6
	9.5 - 20	W 8	W 7	241	955	449	2942	STD	8	TT	107 A6

STD: Standard - HD: Heavy Duty

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Bias



Technologies



Special Compound



Extra Deep Tread

Performance



Traction



High Load Capacity



Self-Cleaning



Durability



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 20"	9.5 - 20	W 8	W 7	241	955	449	2942	HD	8	TT	107 A6
	11.2 - 20	W 10	W 9;9	285	1005	471	3101	STD	8	TT	113 A6
Ø 22"	8.3 - 22	W 7	W 6	205	945	444	2778	STD	8	TT	104 A6
	9.5 - 22	W 8	W 7	244	1005	472	3107	STD	8	TT	110 A6
Ø 24"	8.3 - 24	W 7	W 6	210	1005	474	3014	STD	6	TT	100 A6
	8.3 - 24	W 7	W 6	210	1005	474	3153	STD	8	TT	105 A6
	8.3 - 24	W 7	W 6	210	1005	474	3153	HD	8	TT	105 A6
	9.5 - 24	W 8	W 7	240	1066	500	3260	STD	6	TT	106 A6
	9.5 - 24	W 8	W 7	240	1066	496	3263	STD	8	TT	111 A6
	11.2 - 24	W 10	W 9	285	1105	519	3388	STD	6	TT	110 A6
	11.2 - 24	W 10	W 9	285	1105	517	3403	STD	8	TT	116 A6
	11.2 - 24	W 10	W 9	285	1105	517	3403	STD	10	TT	120 A6
	12.4 - 24	W 11	W 9; W 10	315	1165	544	3557	STD	4	TT	106 A6
	12.4 - 24	W 11	W 9; W 10	315	1165	544	3557	STD	6	TT	115 A6

STD: Standard - HD: Heavy Duty

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Bias



Technologies



Special Compound



Extra Deep Tread

Performance



Traction



High Load Capacity



Self-Cleaning



Durability



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 24"	12.4 - 24	W 11	W 9; W 10	315	1165	544	3557	STD	8	TT	120 A6
	12.4 - 24	W 11	W 9; W 10	315	1165	544	3557	HD	8	TT	120 A6
	13.6 - 24	W 12	W 11	355	1210	562	3674	STD	6	TT	119 A6
	13.6 - 24	W 12	W 11	355	1210	562	3674	STD	8	TT	123 A6
	14.9 - 24	W 13	W 11; W 12	391	1265	575	3792	STD	6	TT	123 A6
	14.9 - 24	W 13	W 11; W 12	391	1265	575	3792	STD	8	TT	128 A6
Ø 26"	11.2 - 26	W 10	W 9	284	1155	541	3463	STD	8	TT	117 A6
	12.4 - 26	W 11	W 10; W 9	315	1210	573	3727	STD	8	TT	121 A6
	13.6 - 26	W 12	W 11	340	1270	580	3774	STD	4	TT	110 A6
	13.6 - 26	W 12	W 11	340	1270	582	3815	STD	6	TT	120 A6
	13.6 - 26	W 12	W 11	340	1270	587	3835	STD	8	TT	126 A6
	13.6 - 26	W 12	W 11	340	1270	589	3774	HD	12	TT	135 A6
Ø 28"	12.4 - 28	W 11	W 9; W 10	315	1260	589	3860	STD	6	TT	117 A6
	12.4 - 28	W 11	W 9; W 10	315	1260	589	3860	STD	8	TT	123 A6

STD: Standard - HD: Heavy Duty

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Bias



Technologies



Special Compound



Extra Deep Tread

Performance



Traction



High Load Capacity



Self-Cleaning



Durability



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS	
		Rec.	Alt.									
Ø 28"	12.4 - 28	W 11	W 9 ; W 10	315	1260	589	3860	STD	12	TT	131 A6	
	13.6 - 28	W 12	W 11	350	1325	614	4013	STD	4	TT	112 A6	
	13.6 - 28	W 12	W 11	350	1325	614	4013	STD	6	TT	121 A6	
	13.6 - 28	W 12	W 11	350	1325	614	4013	STD	8	TT	125 A6	
	13.6 - 28	W 12	W 11	350	1325	616	4007	HD	8	TT	125 A6	
	13.6 - 28	W 12	W 11	350	1325	614	4013	STD	12	TT	134 A6	
	13.6 - 28	W 12	W 11	350	1325	614	4013	HD	12	TT	134 A6	
	14.9 - 28	W 13	W 11 ; W 12	388	1370	636	4246	STD	8	TT	130 A6	
	14.9 - 28	W 13	W 11 ; W 12	388	1370	635	4176	HD	8	TT	130 A6	
	14.9 - 28	W 13	W 11 ; W 12	388	1370	636	4246	STD	12	TT	137 A6	
	14.9 - 28	W 13	W 11 ; W 12	388	1370	636	4246	HD	12	TT	137 A6	
	15.9 - 28	W 13	W 11 ; W 12	410	1420	656	4357	STD	12	TT	140 A6	
	NEWSIZE											
	16.9 - 28	W 15 L	W 14 L	435	1440	674	4496	STD	8	TT	135 A6	
	16.9 - 28	W 15 L	W 14 L	435	1440	674	4496	STD	12	TT	143 A6	

STD: Standard - HD: Heavy Duty

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Bias



Technologies



Special Compound



Extra Deep Tread

Performance



Traction



High Load Capacity



Self-Cleaning



Durability



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 30"	14.9 - 30	W 13	W 11 ; W 12	380	1415	658	4282	STD	8	TT	131 A6
	16.9 - 30	W 15 L	W 14 L	430	1490	687	4535	STD	8	TT	137 A6
	16.9 - 30	W 15 L	W 14 L	430	1490	687	4605	STD	12	TT	143 A6
	18.4 - 30	W 16 L	W 15 L	470	1550	710	4706	STD	10	TT	145 A6
Ø 32"	12.4 - 32	W 11	W 9 ; W 10	315	1370	643	4232	STD	8	TT	124 A6
Ø 34"	16.9 - 34	W 15 L	W 14 L	429	1585	736	4838	STD	8	TT	139 A6
	18.4 - 34	W 16 L	W 15 L	470	1655	768	4866	STD	10	TT	146 A6
Ø 36"	12.4 - 36	W 11	W 9 ; W 10	315	1470	691	4332	STD	8	TT	126 A6
	13.6 - 36	W 12	W 11	345	1520	717	4647	STD	8	TT	129 A6
Ø 38"	13.6 - 38	W 12	W 11	345	1565	729	4818	STD	8	TT	131 A6
	16.9 - 38	W 15 L	W 14 L	429	1685	788	4954	STD	8	TT	141 A6
	18.4 - 38	W 16 L	W 15 L	470	1760	815	5364	STD	10	TT	148 A6

STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference