



US standard



GROWING TOGETHER

# XL GRIP IND3 (ECH)



PRODUCT DATA SHEET





Bias



# XL GRIP IND3 (ECH)

XL GRIP (IND-3) is a bias-ply tire for empty container handlers in stacking and lifting applications. The tire features a strong casing, which provides great durability and as well as a high stability in lift mode.

### Technologies



Heavy Duty

### Performance



Cut and Chip Resistance



Durability



Hard Surfaces



Stability

	US CODE	Tire size	Type	PR	LI/SS	Version	O.D. (In.)	O.W. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
													Rec.	Alt.
Ø 24"	94032785	12.00 - 24	TT	24	-	IND	49.2	12.6	23.0	146.1	30	218	8.5	8.0
Ø 25"	94031894	16.00 - 25	TL	28	-	IND	58.5	18.3	26.9	173.0	37	489	11.25/2.0	13.00/2.0
	94049035	18.00 - 25	TL	32	-	PORT IND	63.6	20.1	29.1	188.2	40	650	13.00/2.5	15.00/2.5
	94049042	18.00 - 25	TL	40	-	PORT IND	63.6	20.1	29.1	188.2	40	692	13.00/2.5	15.00/2.5

IND: Industrial - PORT IND: Port Industrial



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference