


MULTIMAX MP 527

TIRE SIZE	400/70 R 20 IND
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	CARREGADORA COMPACTA / LEVANTADOR TELESCÓPICO / CARREGADORA COMPACTA / LEVANTADOR TELESCÓPICO
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	149 A8/B



DIMENSÕES US STANDARD

CÓDIGO USA	94052073	RC (IN)	129.2
SW (IN)	15.9	RIM REC	13
OD (IN)	42.0	RIM ALT	12 SDC ; 13 SDC ; 14
SLR (IN)	19.4	ECE	E4-106R-002656

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	23	29	35	41	46	51	58	61	64
30	3440	4090	4660	5300	5950	6380	7160	-	-
25	3440	4090	4660	5300	5950	6380	7160	-	-
20	3690	4380	4990	5690	6370	6830	7670	-	-
15	3820	4540	5180	5900	6610	7090	7960	-	-
5 CYC.	4200	5160	6070	6990	7960	8650	9790	10320	10750
STATIC	6440	7910	9310	10710	12200	13270	15000	15830	16480

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.