


# AGRIMAX RT 855

**420/85 R 24**

|              |  |
|--------------|--|
| UM           | US STANDARD  |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | ILAÇLAMA / ÜZÜM HASAT MAKINESİ /<br>TRAKTÖR / BIÇERDÖVER /<br>UYGULAMALI MAKINE          |
| VERSION      | SPECIAL  |
| TIRE TYPE    | TL   |
|              | 137 A8/B   |



## UNDEFINED US STANDARD

|          |          |         |                |
|----------|----------|---------|----------------|
| USA CODE | 94047482 | RC (IN) | 153.5          |
| SW (IN)  | 17.7     | RIM REC | W 15 L         |
| OD (IN)  | 52.1     | RIM ALT | W 14 L ; W 13  |
| SLR (IN) | 22.9     | ECE     | E4-106R-000595 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9    | 12   | 15   | 17   | 20   | 23   |
|-----------|------|------|------|------|------|------|
| 30        | 2790 | 3250 | 3700 | 4170 | 4620 | 5070 |
| 25        | 2790 | 3250 | 3700 | 4170 | 4620 | 5070 |
| 20        | 3000 | 3480 | 3970 | 4460 | 4950 | 5430 |
| 5 LT      | 3750 | 4350 | 4970 | 5580 | 6190 | 6800 |
| 5 HT      | 3000 | 3480 | 3970 | 4460 | 4950 | 5430 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.