


# AW 09

<b>TIRE SIZE</b>	<b>260/70 - 15.3</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	HEUPRESSE / LANDWIRTSCHAFTLICHE GERÄTE / ANHÄNGER / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE / ERNTEMASCHINE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	114 A8
<b>LI/SS FREE ROLLING</b>	126 A8



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	268	<b>RIM REC</b>	9.00
<b>OD (MM)</b>	753	<b>ECE</b>	E4-106R-000373
<b>SLR (MM)</b>	335		
<b>RC (MM)</b>	2206		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.60
10 FR	2380
25 FR	2025
30 FR	1905
40 FR	1700
10 DW	1650
25 DW	1405
30 DW	1320
40 DW	1180

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.