


# TR 315

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>23X10.50 - 12</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  BIAS   |
| <b>MACHINERY</b>    | OUTILLAGE AGRICOLE / RÉCOLTE DES FRUITS / TRANCHEUSE / MOISSONNEUSE / OUTILLAGE AGRICOLE |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |



## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>CODE USA</b> | 94027873 | <b>RC (IN)</b> | 72.4            |
| <b>SW (IN)</b>  | 10.0     | <b>RIM REC</b> | 8½ JA           |
| <b>OD (IN)</b>  | 23.6     | <b>RIM ALT</b> | 7 JA            |
| <b>SLR (IN)</b> | 10.7     | <b>ECE</b>     | E11-106R-005206 |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>56</b> |
| 10               | 2425      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.