

# AGRIMAX TERIS

<b>TIRE SIZE</b>	<b>IF 710/75 R 32 CFO</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	
<b>MACHINERY</b>	HARVESTER / COTTON PICKER
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	183 A8/B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	716	<b>RIM REC</b>	DW 25 B
<b>OD (MM)</b>	1879	<b>RIM ALT</b>	DW 23 B
<b>SLR (MM)</b>	851	<b>ECE</b>	E11-106R-005025
<b>RC (MM)</b>	5653	<b>SRI</b>	875

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.4	1.6	2.0	2.4	2.8	3.2
50	3415	4025	4640	5775	6300	6915	7440	8140	8750
40	3415	4025	4640	5775	6300	6915	7440	8140	8750
30	3655	4310	4965	6185	6745	7400	7965	8710	9365
15 CYC*	5295	6240	7190	8955	9770	10720	11535	12620	13565
10 CYC*	6145	7245	8350	10395	11340	12445	13390	14650	15750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.