

## AGRIMAX RT 657

|                  |                                          |
|------------------|------------------------------------------|
| <b>TIRE SIZE</b> | <b>650/65 R 38</b>                       |
| <b>UM</b>        | US STANDARD                              |
| <b>MACHINERY</b> | VINEYARD HARVESTER / TRACTOR / HARVESTER |
| <b>VERSION</b>   | STANDARD                                 |
| <b>TL/TT</b>     | TL                                       |
| <b>LI/SS</b>     | 163 D ; 166 A8                           |



### DIMENSIONS US STANDARD

|                 |          |                |                   |
|-----------------|----------|----------------|-------------------|
| <b>USA CODE</b> | 94021383 | <b>RC (IN)</b> | 215.9             |
| <b>SW (IN)</b>  | 25.4     | <b>RIM REC</b> | DW 20 B           |
| <b>OD (IN)</b>  | 71.3     | <b>RIM ALT</b> | DW 21 B ; DW 23 B |
| <b>SLR (IN)</b> | 32.7     | <b>ECE</b>     | E4-106R-000624    |

### LOAD CAPACITY (LBS/TIRE)

| MPH / PSI   | 9    | 12   | 15   | 17    | 20    | 23    | 29    | 35    |
|-------------|------|------|------|-------|-------|-------|-------|-------|
| <b>40</b>   | 5160 | 6020 | 6780 | 7530  | 8280  | 8930  | 9890  | 10700 |
| <b>30</b>   | 5420 | 6330 | 7120 | 7900  | 8700  | 9370  | 10390 | 11290 |
| <b>25</b>   | 5610 | 6550 | 7360 | 8180  | 9010  | 9700  | 10760 | 11680 |
| <b>20</b>   | 5940 | 6930 | 7790 | 8660  | 9520  | 10270 | 11390 | 12370 |
| <b>5 LT</b> | 6920 | 8070 | 9080 | 10090 | 11100 | 11960 | 13260 | 14410 |
| <b>5 HT</b> | 5940 | 6930 | 7790 | 8660  | 9520  | 10270 | 11390 | 12370 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.