

AGRIMAX RT 955

TIRE SIZE	270/80 R 36
UM	IS STANDARD
MACHINERY	PULVÉRISATEUR / MACHINE À VENDANGER / MOISSONNEUSE / OUTILLAGE AGRICOLE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	134 A8/B



DIMENSIONS IS STANDARD

SW (MM)	275	ECE	E11-106R-006758
OD (MM)	1346	SRI	650
SLR (MM)	629	TRA CODE	R1
RC (MM)	4090	TREAD DEPTH (MM)	34,5
RIM REC	W9	TKPH (TK/H)	0
RIM ALT	W8; W10		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6	4.0
50	745	870	1000	1125	1255	1360	1510	1590	1740	1890	2015	2120
40	745	870	1000	1125	1255	1360	1510	1590	1740	1890	2015	2120
30	795	935	1070	1205	1340	1455	1615	1705	1865	2025	2160	2270
10	1115	1305	1495	1690	1880	2040	2260	2385	2610	2835	3025	3180

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.