


RIDEMAX FL 693 M



TIRE SIZE	500/60 R 22.5
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TANKER / TRAILER / IMPLEMENTS
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	163 D

DIMENSIONS US STANDARD

USA CODE	94069446	RC (IN)	142.7
SW (IN)	19.8	RIM REC	AG 16.00
OD (IN)	46.1	RIM ALT	15.00; 17.00
SLR (IN)	21.4	ECE	E11-106R-007203

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	23	29	35	41	46	52	58	65	73	80	87
45	3250	4030	4410	5100	5780	6380	6960	7640	8140	8620	9210	9790
40	3550	4410	4840	5590	6350	6990	7640	8390	8930	9460	10110	10750
30	4300	5340	5860	6770	7690	8460	9240	10160	10810	11460	12240	13010
25	4830	6000	6590	7610	8640	9510	10390	11410	12140	12870	13750	14620
15	5620	6970	7650	8850	10040	11050	12070	13250	14110	14960	15980	16990
5	6400	7940	8710	10070	11420	12580	13750	15090	16060	17030	18190	19350

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.