


# AGRIMAX V-FLECTO



<b>TIRE SIZE</b>	<b>VF 520/85 R 42</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRATOR DE ALTA POTENCIA / TRATOR
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	180 D

## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94067237	<b>RC (IN)</b>	230.0
<b>SW (IN)</b>	21.1	<b>RIM REC</b>	DW 18 L
<b>OD (IN)</b>	76.8	<b>ECE</b>	E11-106R-007169
<b>SLR (IN)</b>	34.5	<b>TRA CODE</b>	R1W

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	46
45	6260	7390	8510	9480	10590	11560	12690	13650	16050
<b>FROM 40 TO 25</b>	6880	8110	9350	10410	11640	12700	13930	14990	17640
20	7020	8280	9530	10610	11880	12960	14220	15300	17990
12	7150	8440	9720	10820	12110	13220	14490	15600	18340
5	7570	8930	10280	11450	12810	13980	15330	16490	19400
<b>UPTO 5 CYC WITH FRONT LOADER</b>	9630	11360	13090	14570	16300	17780	19510	20990	24690
5 HT	7020	8280	9530	10610	11880	12960	14220	15300	17990

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.