

# BK 826

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | <b>9.00 - 16</b>  |
| <b>UM</b>           | IS STANDARD   |
| <b>CONSTRUCTION</b> | ⊠ BIAS  |
| <b>MACHINERY</b>    | SLÄPVAGN / ARBETSFORDON /<br>SKÖRDEMASKIN / SLÄPVAGN /<br>GRÄVLASTARE |
| <b>VERSION</b>      | HARVESTER SPECIAL   |
| <b>TIRE TYPE</b>    | TT  |



## DIMENSIONER IS STANDARD

|                |        |           |    |
|----------------|--------|-----------|----|
| <b>SW (MM)</b> | 265    | <b>PR</b> | 16 |
| <b>OD (MM)</b> | 925    |           |    |
| <b>RIM REC</b> | 6.50 H |           |    |
| <b>RIM ALT</b> | 6.00 G |           |    |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>7.25</b> |
| 30                | 2300        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.