


RIDEMAX FL 693 M



| | |
|---------------------|--|
| TIRE SIZE | 560/55 R 22.5 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | CAMIÓN CISTERNA / REMOLQUE / MAQUINARIA AGRÍCOLA |
| VERSIÓN | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 162 D |

DIMENSIONES US STANDARD

| | | | |
|-------------------|----------|----------------|-----------------|
| CÓDIGO USA | 94067626 | RC (IN) | 142.3 |
| SW (IN) | 21.4 | RIM REC | AG 16.00 |
| OD (IN) | 46.5 | RIM ALT | 17.00; 20.00 |
| SLR (IN) | 21.0 | ECE | E11-106R-006972 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 | 65 | 73 |
|-----------|------|------|------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 3630 | 4390 | 4860 | 5630 | 6390 | 7050 | 7730 | 8490 | 9060 | 9530 |
| 40 | 3980 | 4820 | 5350 | 6180 | 7020 | 7750 | 8490 | 9330 | 9950 | 10470 |
| 30 | 4820 | 5830 | 6470 | 7480 | 8500 | 9380 | 10270 | 11290 | 12050 | 12670 |
| 25 | 5410 | 6560 | 7260 | 8410 | 9550 | 10550 | 11540 | 12680 | 13540 | 14240 |
| 15 | 6290 | 7620 | 8440 | 9770 | 11090 | 12250 | 13400 | 14730 | 15720 | 16540 |
| 5 | 7160 | 8670 | 9620 | 11120 | 12630 | 13950 | 12580 | 16780 | 17910 | 18850 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.