

# AS 504

|                           |  |
|---------------------------|--|
| <b>TIRE SIZE</b>          | <b>7.00 - 12</b>   |
| <b>UM</b>                 | US STANDARD  |
| <b>CONSTRUCTION</b>       | ⊠ BIAS   |
| <b>MACHINERY</b>          | ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК |
| <b>VERSION</b>            | STANDARD   |
| <b>TIRE TYPE</b>          | TT   |
| <b>LI/SS DRIVE WHEEL</b>  | 75 A8  |
| <b>LI/SS FREE ROLLING</b> | 88 A8  |



## РАЗМЕРЫ US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94019229 | <b>RC (IN)</b> | 80.7           |
| <b>SW (IN)</b>  | 7.4      | <b>RIM REC</b> | 4.5            |
| <b>OD (IN)</b>  | 26.9     | <b>ECE</b>     | E4-106R-002207 |
| <b>SLR (IN)</b> | 12.2     | <b>PR</b>      | 4              |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 25   |
|-----------|------|
| 5 FR      | 1730 |
| 15 FR     | 1470 |
| 20 FR     | 1380 |
| 25 FR     | 1230 |
| 5 DW      | 1190 |
| 15 DW     | 1010 |
| 20 DW     | 950  |
| 25 DW     | 850  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.