


# FL 630 SUPER

<b>TIRE SIZE</b>	<b>650/55 R 26.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SPARGITORE / AUTOBOTTE / RIMORCHIO / ATTREZZI AGRICOLI
<b>VERSIONE</b>	HD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	178 D



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94048953	<b>RC (IN)</b>	169.0
<b>SW (IN)</b>	25.4	<b>RIM REC</b>	AG 20.00
<b>OD (IN)</b>	54.7	<b>ECE</b>	E11-106R-003006
<b>SLR (IN)</b>	24.7		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	17	23	29	35	41	46	52	58	73	87
40	4130	5130	6120	7440	8600	9920	11240	12070	13390	14720	15540	16530
30	5000	6210	7410	9010	10410	12000	13610	14600	16280	17810	18820	20010
25	5620	6980	8320	10120	11690	13490	15300	16420	18220	20020	21140	22490
20	6250	7750	9250	11240	12980	14980	16990	18230	20230	22220	23480	24970
15	6540	8100	9670	11760	13590	15670	17770	19080	21160	23260	24560	26120
5	7440	9230	11010	13390	15480	17860	20240	21730	24110	26490	27980	29760

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.