


# AGRIMAX V- FLECTO

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>VF 710/75 R 42</b>  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | MOTORSTARK TRAKTOR / TRAKTOR   |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 184 D  |



## DIMENSIONER US STANDARD

|                 |          |                |                  |
|-----------------|----------|----------------|------------------|
| <b>USA CODE</b> | 94075447 | <b>RC (IN)</b> | 252.4            |
| <b>SW (IN)</b>  | 28.7     | <b>RIM REC</b> | DW 24 B          |
| <b>OD (IN)</b>  | 84.6     | <b>RIM ALT</b> | DW 23 B; DW 25 B |
| <b>SLR (IN)</b> | 36.9     | <b>ECE</b>     | E11-106R-009074  |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI                            | 9     | 12    | 15    | 17    | 20    | 23    | 29    |
|--------------------------------------|-------|-------|-------|-------|-------|-------|-------|
| 45                                   | 9030  | 10470 | 11920 | 13540 | 14980 | 16420 | 18050 |
| <b>FROM 40 TO 25</b>                 | 9920  | 11510 | 13090 | 14880 | 16470 | 18050 | 19840 |
| 20                                   | 10120 | 11730 | 13350 | 15180 | 16790 | 18410 | 20240 |
| 12                                   | 10320 | 11960 | 13610 | 15480 | 17120 | 18770 | 20630 |
| 5                                    | 10910 | 12650 | 14400 | 16370 | 18110 | 19850 | 21820 |
| <b>*UPTO 5 CYC WITH FRONT LOADER</b> | 13890 | 16100 | 18330 | 20830 | 23050 | 25270 | 27780 |
| 5 HT                                 | 10120 | 11730 | 13350 | 15180 | 16790 | 18410 | 20240 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.