

FLOTATION 648

TIRE SIZE	600/50 - 22.5
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	BALPRESS / SKÖRDEMASKIN / SPRIDARE / SKÖRDEMASKIN / ARBETSFORDON
VERSION	DUAL BEAD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	156 A8/152 B
LI/SS FREE ROLLING	169 A8/165 B



DIMENSIONER US STANDARD

USA CODE	94045266	RC (IN)	137.8
SW (IN)	24.1	RIM REC	AG 20.00
OD (IN)	46.1	ECE	E11-106R-004392
SLR (IN)	20.1	PR	20

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	44	45	46
5 FR	17240	17580	17900
10 FR	15510	15820	16110
20 FR	13790	14060	14320
25 FR	12310	12550	12790
30 FR	11080	11300	11350
5 DW	11880	12110	12350
10 DW	10690	10900	11110
20 DW	9500	9690	9880
25 DW	8490	8650	8820
30 DW	7640	7790	7830

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.