

# FLOTATION 648

<b>TIRE SIZE</b>	<b>700/40 - 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	BALER / HAY HARVESTER / SPREADER / HARVESTER / IMPLEMENTS
<b>VERSION</b>	HD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	160 A8/156 B
<b>LI/SS FREE ROLLING</b>	173 A8/169 B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94027903	<b>RC (IN)</b>	139.3
<b>SW (IN)</b>	27.6	<b>RIM REC</b>	AG 24.00
<b>OD (IN)</b>	46.1	<b>ECE</b>	E4-106R-002281
<b>SLR (IN)</b>	20.1	<b>PR</b>	18

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	41	44	46
5 FR	18550	19230	20060
10 FR	16700	17390	18050
20 FR	14840	15450	16050
25 FR	13250	13800	14330
30 FR	11930	12420	12790
5 DW	12840	13380	13890
10 DW	11550	12040	12500
20 DW	10270	10700	11110
25 DW	9170	9560	9920
30 DW	8260	8600	8820

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.