


# EARTHMAX SR 31

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>26.5 R 25</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | LOADER / DOZER / ARTICULATED<br>DUMP TRUCK / LOADER / DOZER                              |
| <b>VERSION</b>      | CUT RESISTANT COMPOUND   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 209 A2   |



## DIMENSIONS IS STANDARD

|                 |           |                    |    |
|-----------------|-----------|--------------------|----|
| <b>OD (MM)</b>  | 1742      | <b>TRA CODE</b>    | L3 |
| <b>SLR (MM)</b> | 766       | <b>STAR RATING</b> | ★★ |
| <b>RC (MM)</b>  | 5200      |                    |    |
| <b>RIM REC</b>  | 22.00/3.0 |                    |    |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 5.25  | 5.50  | 5.75  | 6.00  | 6.25  | 6.50  |
|------------|-------|-------|-------|-------|-------|-------|
| 10         | 15500 | 16000 | 16500 | 17000 | 18000 | 18500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.