

# AS 504

|                           |   |
|---------------------------|---|
| <b>TIRE SIZE</b>          | <b>10.0/75 - 15.3</b>   |
| <b>UM</b>                 | IS STANDARD   |
| <b>CONSTRUCTION</b>       | ❖ BIAS  |
| <b>MACHINERY</b>          | LEVANTADOR TELESCÓPICO /<br>REBOQUE PARA OS CAMPOS /<br>IMPLEMENTOS AGRÍCOLAS /<br>LEVANTADOR TELESCÓPICO |
| <b>VERSÃO</b>             | STANDARD  |
| <b>TIRE TYPE</b>          | TL  |
| <b>LI/SS DRIVE WHEEL</b>  | 106 A8  |
| <b>LI/SS FREE ROLLING</b> | 119 A8  |



## DIMENSÕES IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 264  | <b>RIM REC</b> | 9.00            |
| <b>OD (MM)</b>  | 785  | <b>ECE</b>     | E11-106R-003509 |
| <b>SLR (MM)</b> | 360  | <b>PR</b>      | 8               |
| <b>RC (MM)</b>  | 2404 | <b>SRI</b>     | 360             |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>3.10</b> |
|-------------------|-------------|
| 10 FR             | 1905        |
| 25 FR             | 1620        |
| 30 FR             | 1525        |
| 40 FR             | 1360        |
| 10 DW             | 1330        |
| 25 DW             | 1130        |
| 30 DW             | 1065        |
| 40 DW             | 950         |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.