

# FLOTATION 648

<b>TYRE SIZE</b>	<b>400/60 - 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	HAY HARVESTER / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TYRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	144 A8/140 B
<b>LI/SS FREE ROLLING</b>	156 A8/152 B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94006311	<b>RC (IN)</b>	127.3
<b>SW (IN)</b>	15.7	<b>RIM REC</b>	AG 11.75
<b>OD (IN)</b>	42.1	<b>ECE</b>	E4-106R-002336
<b>SLR (IN)</b>	18.7	<b>PR</b>	16

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	22	36	51
5 FR	7520	10140	12350
10 FR	6770	9130	11110
20 FR	6010	8110	9880
25 FR	5370	7240	8820
30 FR	4830	6510	7830
5 DW	5260	7100	8640
10 DW	4740	6390	7780
20 DW	4210	5680	6910
25 DW	3760	5070	6170
30 DW	3380	4560	5510

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.