DATA SHEET

PRINTED ON
22-04-2026

AGRIMAX TERIS

TYRE SIZE	**520/85 R 42**
UM	US STANDARD
CONSTRUCTION	RADIAL
VERSION	STANDARD
TYRE TYPE	TL
LI/SS	168 D

DIMENSIONS US STANDARD

USA CODE	94044634	**RC (IN)**	230.4
SW (IN)	20.3	**RIM REC**	DW 16 L
OD (IN)	76.8	**RIM ALT**	W15L; DW15L; DD16L; W16L; DD18L; DW18L; W18L
SLR (IN)	35.0	**ECE**	E4-106R-001829

LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	46	55
40	4080	4820	5560	6170	6920	7540	8770	10010	11240	12350	-
30	4290	5060	5840	6480	7260	7910	9200	10500	11810	12960	-
25	4460	5280	6100	6770	7580	8260	9610	10960	12310	13520	-
20	4700	5540	6390	7100	7960	8660	10090	11510	12930	14200	-
15	4840	5710	6590	7320	8200	8940	10390	11860	13330	14640	-
5	6120	7230	8330	9260	10370	11300	13150	15000	16850	18520	-
5 CYC*	-	-	-	-	-	-	-	-	-	-	20990

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..