

## AGRIMAX RT 657

|                  |                                          |
|------------------|------------------------------------------|
| <b>TIRE SIZE</b> | <b>540/65 R 34</b>                       |
| <b>UM</b>        | IS STANDARD                              |
| <b>MACHINERY</b> | VINEYARD HARVESTER / TRACTOR / HARVESTER |
| <b>VERSION</b>   | STANDARD                                 |
| <b>TL/TT</b>     | TL                                       |
| <b>LI/SS</b>     | 152 D ; 155 A8                           |



### DIMENSIONS IS STANDARD

|                 |        |                         |                |
|-----------------|--------|-------------------------|----------------|
| <b>SW (MM)</b>  | 530    | <b>RIM ALT</b>          | W 18 L         |
| <b>OD (MM)</b>  | 1566   | <b>ECE</b>              | E4-106R-000652 |
| <b>SLR (MM)</b> | 712    | <b>SRI</b>              | 750            |
| <b>RC (MM)</b>  | 4742   | <b>TRA CODE</b>         | R1W            |
| <b>RIM REC</b>  | W 16 L | <b>TREAD DEPTH (MM)</b> | 49,5           |

### LOAD CAPACITY (KG/TIRE)

| KM/H / BAR   | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  |
|--------------|------|------|------|------|------|------|------|------|
| <b>65</b>    | 1705 | 1990 | 2240 | 2485 | 2735 | 2950 | 3270 | 3550 |
| <b>50</b>    | 1795 | 2090 | 2350 | 2615 | 2875 | 3100 | 3435 | 3730 |
| <b>40</b>    | 1860 | 2170 | 2445 | 2715 | 2985 | 3220 | 3565 | 3875 |
| <b>30</b>    | 1965 | 2290 | 2575 | 2860 | 3150 | 3395 | 3760 | 4085 |
| <b>10 LT</b> | 2285 | 2670 | 3000 | 3335 | 3670 | 3955 | 4380 | 4760 |
| <b>10 HT</b> | 1965 | 2290 | 2575 | 2860 | 3150 | 3395 | 3760 | 4085 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.