


FLOTATION 648

| | |
|---------------------------|--|
| TIRE SIZE | 600/55 - 26.5 |
| UM | IS STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | EMPACADORA DE HENO / COSECHADORA / ESPARCIDOR / COSECHADORA / MAQUINARIA AGRÍCOLA |
| VERSIÓN | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 160 A8/157 B |
| LI/SS FREE ROLLING | 172 A6/169 B |



DIMENSIONES IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 611 | RIM REC | AG 20.00 |
| OD (MM) | 1354 | ECE | E11-106R-004556 |
| SLR (MM) | 581 | PR | 18 |
| RC (MM) | 4017 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 2.70 | 2.80 | 2.90 |
|------------|------|------|------|
| 10 FR | 8455 | 8640 | 8820 |
| 20 FR | 7610 | 7775 | 7940 |
| 30 FR | 6765 | 6910 | 7055 |
| 40 FR | 6040 | 6170 | 6300 |
| 50 FR | 5435 | 5555 | 5800 |
| 10 DW | 6040 | 6175 | 6300 |
| 20 DW | 5435 | 5555 | 5670 |
| 30 DW | 4835 | 4940 | 5040 |
| 40 DW | 4315 | 4410 | 4500 |
| 50 DW | 3885 | 3970 | 4125 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.