

# AGRIMAX V-FLECTO



|                     |                                                                                          |
|---------------------|------------------------------------------------------------------------------------------|
| <b>TYRE SIZE</b>    | <b>VF 650/60 R 42</b>                                                                    |
| <b>UM</b>           | IS STANDARD                                                                              |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | HIGH-POWER TRACTOR / TRACTOR                                                             |
| <b>VERSION</b>      | STANDARD                                                                                 |
| <b>TL/TT</b>        | TL                                                                                       |
| <b>LI/SS</b>        | 174 D                                                                                    |

## DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 660  | <b>RIM REC</b> | DW 23 B         |
| <b>OD (MM)</b>  | 1845 | <b>RIM ALT</b> | DW21B           |
| <b>SLR (MM)</b> | 834  | <b>ECE</b>     | E11-106R-008774 |
| <b>RC (MM)</b>  | 5564 | <b>SRI</b>     | 875             |

## LOAD CAPACITY (KG/TYRE)

| KM/H / BAR                     | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  |
|--------------------------------|------|------|------|------|------|------|------|------|
| 70                             | 2800 | 3230 | 3715 | 4140 | 4630 | 5055 | 5665 | 6095 |
| FROM 65 TO 40                  | 3080 | 3550 | 4085 | 4555 | 5090 | 5560 | 6230 | 6700 |
| 30                             | 3140 | 3615 | 4165 | 4640 | 5190 | 5665 | 6350 | 6830 |
| 20                             | 3200 | 3690 | 4245 | 4735 | 5290 | 5780 | 6475 | 6965 |
| 10                             | 3390 | 3905 | 4495 | 5010 | 5600 | 6115 | 6850 | 7370 |
| *UPTO 10 CYC WITH FRONT LOADER | 4310 | 4970 | 5720 | 6375 | 7125 | 7785 | 8720 | 9380 |
| 10 HT                          | 3140 | 3615 | 4165 | 4640 | 5190 | 5665 | 6350 | 6830 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.