

# AS 504

<b>TIRE SIZE</b>	<b>12.5/80 - 18</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	SOLLEVATORE TELESOPICO / RIMORCHIO DA CAMPO / ATTREZZI AGRICOLI / SOLLEVATORE TELESOPICO
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	138 A8
<b>LI/SS FREE ROLLING</b>	150 A8



## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	308	<b>RIM REC</b>	W 9
<b>OD (MM)</b>	987	<b>RIM ALT</b>	9; 11
<b>SLR (MM)</b>	438	<b>ECE</b>	E11-106R-004348
<b>RC (MM)</b>	2892	<b>PR</b>	18

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>5.50</b>
10 FR	4690
25 FR	3985
30 FR	3750
40 FR	3350
10 DW	3305
25 DW	2810
30 DW	2645
40 DW	2360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.