


# AGRIMAX RT 955

<b>TIRE SIZE</b>	<b>340/85 R 46</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	IRRORAZIONE / VENDEMMIATRICE / MIETITREBBIA / ATTREZZI AGRICOLI
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	150 A8/B



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94044726	<b>RC (IN)</b>	210.5
<b>SW (IN)</b>	13.9	<b>RIM REC</b>	W 12
<b>OD (IN)</b>	68.7	<b>RIM ALT</b>	W 11
<b>SLR (IN)</b>	32.5	<b>ECE</b>	E4-106R-001828

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	52	58
30	3190	4140	5030	5470	5840	6430	6940	7400	-
25	3190	4140	5030	5470	5840	6430	6940	7400	-
20	3410	4430	5380	5850	6250	6880	7430	7900	-
5	4550	5870	7100	7760	8310	9090	9870	10530	11080

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.