

# MULTIMAX MP 527

**340/80 R 18 IND****UM** US STANDARD**CONSTRUCTION**  RADIAL**MACHINERY** KÜÇÜK YÜKLEYİCİ / TELESKOPIK  
YÜKLEYİCİ / KÜÇÜK YÜKLEYİCİ /  
TELESKOPIK YÜKLEYİCİ**VERSION** STANDARD**TIRE TYPE** TL

143 A8/B



## UNDEFINED US STANDARD

<b>USA CODE</b>	94048694	<b>RC (IN)</b>	119.2
<b>SW (IN)</b>	13.5	<b>RIM REC</b>	11 ; 11 SDC ; W 11
<b>OD (IN)</b>	39.4	<b>RIM ALT</b>	W 10 ; 12 ; 12 SDC
<b>SLR (IN)</b>	17.9	<b>ECE</b>	E4-106R-002981

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	23	29	35	41	46	51	58	61	64
30	2890	3430	3910	4450	4990	5360	6010	-	-
25	2890	3430	3910	4450	4990	5360	6010	-	-
20	3100	3670	4190	4770	5350	5730	6440	-	-
15	3210	3800	4340	4940	5540	5940	6670	-	-
5 CYC.	3530	4330	5100	5860	6680	7260	8210	8660	9020
STATIC	5400	6640	7810	8990	10230	11130	12590	13270	13820

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.