


AGRIMAX V- FLECTO



TIRE SIZE	VF 600/60 R 30
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRATTORE A ELEVATA POTENZA / TRATTORE
VERSIONE	STANDARD
TIRE TYPE	TL
LI/SS	158 D

DIMENSIONI IS STANDARD

SW (MM)	595	RIM REC	DW 20 B
OD (MM)	1485	RIM ALT	DW 18 L; DW 21 B
SLR (MM)	649	ECE	E11-106R-002979
RC (MM)	4404	SRI	700

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
70	2120	2475	2820	3170	3515	3865
FROM 65 TO 40	2335	2720	3100	3485	3865	4250
30	2380	2770	3160	3550	3940	4335
20	2425	2825	3220	3620	4015	4420
10	2565	2990	3410	3830	4250	4675
*UPTO 10 CYC WITH FRONT LOADER	3270	3805	4340	4875	5410	5950
10HT	2380	2770	3160	3550	3940	4335

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.