


AGRIMAX PROHARVEST

TIRE SIZE	VF 800/70 R 32
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	MOISSONNEUSE
VERSION	STEEL BELTED
TIRE TYPE	TL
LI/SS	187 D



DIMENSIONS US STANDARD

CODE USA	94512263	RC (IN)	229.0
SW (IN)	31.7	RIM REC	DW 28 B
OD (IN)	76.1	RIM ALT	DW 27 B; DW 30 B
SLR (IN)	33.3	ECE	E11-106R-0010664

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	9180	10550	12110	13680	15240	16810	18370	19550
FROM 40 TO 25	10100	11610	13330	15050	16770	18480	20200	21490
20	10300	11840	13590	15340	17100	18850	20600	21920
12	10500	12070	13860	15640	17430	19220	21010	22350
5	11110	12760	14650	16540	18440	20330	22220	23640
UPTO 20 CYC	11460	13170	15120	17070	19020	20980	22930	24390
UPTO 10 CYC	13680	15720	18050	20380	22710	25040	27370	29120
UPTO 5 CYC	14990	17230	19770	22330	24890	27440	29990	31910
10HT	10300	11840	13590	15340	17100	18850	20600	21920

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.