

# TR 117

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | <b>14.9 - 24</b>                              |
| <b>UM</b>           | US STANDARD                                   |
| <b>CONSTRUCTION</b> | ⊠ BIAS  |
| <b>MACHINERY</b>    | ROTERANDE BEVATTNINGSMASKIN /<br>ARBETSFORDON |
| <b>VERSION</b>      | STANDARD                                      |
| <b>TIRE TYPE</b>    | TL  |
| <b>LI/SS</b>        | 124 A8  |



## DIMENSIONER US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94031429 | <b>RC (IN)</b> | 144.1           |
| <b>SW (IN)</b>  | 14.9     | <b>RIM REC</b> | W 13            |
| <b>OD (IN)</b>  | 49.0     | <b>RIM ALT</b> | W 11; W 12      |
| <b>SLR (IN)</b> | 22.6     | <b>ECE</b>     | E11-106R-004530 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 26   | 34   |
|-----------|------|------|
| 25        | 3520 | ---  |
| CREEP     | ---  | 7440 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.