

# W 207

|                     |              |
|---------------------|--------------|
| <b>TIRE SIZE</b>    | AT 25X12 - 9 |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> | ⊠ BIAS       |
| <b>MACHINERY</b>    | VEHÍCULO ATV |
| <b>VERSIÓN</b>      | STANDARD     |
| <b>TIRE TYPE</b>    | TL           |



## DIMENSIONES US STANDARD

|                   |          |                |                 |
|-------------------|----------|----------------|-----------------|
| <b>CÓDIGO USA</b> | 94001637 | <b>RIM ALT</b> | 9.0 AT; 10.0 AT |
| <b>SW (IN)</b>    | 11.8     | <b>ECE</b>     | E11-75R-004629  |
| <b>OD (IN)</b>    | 24.9     | <b>PR</b>      | 6               |
| <b>RIM REC</b>    | 9.5 AT   |                |                 |

## LOAD CAPACITY (LBS/TIRE)

|                  |          |
|------------------|----------|
| <b>MPH / PSI</b> | <b>7</b> |
| 62               | 495      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.