


# EARTHMAX SR 431

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>18.00 R 25</b>  |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | STEL DUMPER  |
| <b>VERSION</b>      | CUT RESISTANT COMPOUND   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 185 B  |



## DIMENSIONER IS STANDARD

|                 |           |                    |    |
|-----------------|-----------|--------------------|----|
| <b>OD (MM)</b>  | 1660      | <b>TRA CODE</b>    | E4 |
| <b>SLR (MM)</b> | 760       | <b>STAR RATING</b> | ★★ |
| <b>RC (MM)</b>  | 5040      |                    |    |
| <b>RIM REC</b>  | 13.00/2.5 |                    |    |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 5.00 | 5.25 | 5.50 | 5.75 | 6.00 | 6.25 | 6.50 | 6.75 | 7.00 |
|------------|------|------|------|------|------|------|------|------|------|
| 50         | 7300 | 7500 | 7750 | 8000 | 8250 | 8500 | 8750 | 9000 | 9250 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.