

# AS 504

<b>TIRE SIZE</b>	<b>16.0/70 - 20</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	
<b>MACHINERY</b>	TELEHANDLER / FIELD TRAILER / IMPLEMENTS / TELEHANDLER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	142 A8
<b>LI/SS FREE ROLLING</b>	154 A8



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	418	<b>RIM REC</b>	13
<b>OD (MM)</b>	1097	<b>RIM ALT</b>	12 SDC; 14; 13 SDC
<b>SLR (MM)</b>	487	<b>ECE</b>	E4-106R-001876
<b>RC (MM)</b>	3214	<b>PR</b>	14

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>3.50</b>
<b>10 FR</b>	5250
<b>25 FR</b>	4465
<b>30 FR</b>	4200
<b>40 FR</b>	3750
<b>10 DW</b>	3710
<b>25 DW</b>	3155
<b>30 DW</b>	2970
<b>40 DW</b>	2650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.