

# AS 504

|                           |   |
|---------------------------|---|
| <b>TIRE SIZE</b>          | <b>10.0/75 - 15.3</b>   |
| <b>UM</b>                 | IS STANDARD   |
| <b>CONSTRUCTION</b>       |  BIAS            |
| <b>MACHINERY</b>          | ELEVADOR TELESCÓPICO /<br>EWMOLQUE PARA CAMPOS /<br>MAQUINARIA AGRÍCOLA / ELEVADOR<br>TELESCÓPICO |
| <b>VERSIÓN</b>            | INDUSTRIAL  |
| <b>TIRE TYPE</b>          | TL  |
| <b>LI/SS DRIVE WHEEL</b>  | 106 A8  |
| <b>LI/SS FREE ROLLING</b> | 119 A8  |



## DIMENSIONES IS STANDARD

|                 |      |                |      |
|-----------------|------|----------------|------|
| <b>SW (MM)</b>  | 264  | <b>RIM REC</b> | 9.00 |
| <b>OD (MM)</b>  | 785  | <b>PR</b>      | 8    |
| <b>SLR (MM)</b> | 360  | <b>SRI</b>     | 360  |
| <b>RC (MM)</b>  | 2404 |                |      |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 3.10 |
|------------|------|
| 10 FR      | 1905 |
| 25 FR      | 1620 |
| 30 FR      | 1525 |
| 40 FR      | 1360 |
| 10 DW      | 1330 |
| 25 DW      | 1130 |
| 30 DW      | 1065 |
| 40 DW      | 950  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.