


MULTIMAX MP 522



TIRE SIZE	380/75 R 20 IND
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	KOMPAKTHJULLASTARE / TELESKOPLASTARE / KOMPAKTHJULLASTARE / TELESKOPLASTARE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	148 A8/B

DIMENSIONER IS STANDARD

SW (MM)	384	RIM REC	W 12
OD (MM)	1074	RIM ALT	W 11; 11; 12
SLR (MM)	483	ECE	E11-106R-002963
RC (MM)	3251	SRI	500

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.6	2.0	2.4	2.8	3.2	3.6	3.8	4.0	4.2	4.4
50	1500	1770	2040	2305	2575	2860	3005	3150	-	-
40	1500	1770	2040	2305	2575	2860	3005	3150	-	-
30	1610	1900	2195	2490	2780	3075	3220	3370	-	-
25	1670	1975	2280	2585	2890	3195	3350	3500	-	-
10 CYC.	1850	2260	2670	3080	3490	3900	4110	4315	4520	4730
STATIC	2840	3470	4100	4730	5360	5990	6305	6620	6935	7250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.