

# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>480/80 R 50</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	176 A8



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	489	<b>RIM REC</b>	DW 16 L
<b>OD (MM)</b>	2036	<b>RIM ALT</b>	DW 15 L; W 15 L
<b>SLR (MM)</b>	945	<b>ECE</b>	E4-106R-001495
<b>RC (MM)</b>	6183	<b>SRI</b>	975

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4	5.0
<b>50</b>	2060	2365	2715	3065	3415	3765	4070	4375	4760	5185	5470	5825	6320	7100
<b>40</b>	2060	2365	2715	3065	3415	3765	4070	4375	4760	5185	5470	5825	6320	7100
<b>30</b>	2205	2530	2905	3280	3655	4030	4360	4685	5095	5550	5855	6235	6765	7600
<b>10 LT</b>	2760	3170	3640	4110	4575	5045	5455	5865	6380	6950	7330	7805	8470	9515
<b>10 HT</b>	2205	2530	2905	3280	3655	4030	4360	4685	5095	5550	5855	6235	6765	7600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.