


AS 509

TIRE SIZE	550/45 - 22.5
UM	US STANDARD
CONSTRUCTION	 BIAS
MACHINERY	PRESSE À PAILLE / OUTILLAGE AGRICOLE / REMORQUE / MOISSONNEUSE / OUTILLAGE AGRICOLE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	141 A8/137 B
LI/SS FREE ROLLING	153 A8/149 B



DIMENSIONS US STANDARD

CODE USA	94064878	RC (IN)	128.0
SW (IN)	21.3	RIM REC	AG 16.00
OD (IN)	41.9	ECE	E11-106R-006445
SLR (IN)	18.9	PR	12

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	22	26	30
5 FR	9260	10300	11260
10 FR	8330	9260	10140
20 FR	7410	8230	9020
25 FR	6610	7350	8050
30 FR	5950	6610	7160
5 DW	6530	7260	7950
10 DW	5870	6540	7150
20 DW	5220	5820	6360
25 DW	4660	5190	5680
30 DW	4200	4670	5070

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.