


FL 639

| | |
|---------------------|--|
| TIRE SIZE | 560/45 R 22.5 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | SPREADER / IMPLEMENTS |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 152 D ; 163 A8 |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94034260 | RC (IN) | 130.0 |
| SW (IN) | 21.4 | RIM REC | AG 16.00 |
| OD (IN) | 42.4 | ECE | E4-106R-000627 |
| SLR (IN) | 19.1 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12 | 15 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 |
|-----------|------|------|------|------|------|------|-------|-------|-------|-------|
| 45 | 2290 | 2650 | 3000 | 3570 | 4210 | 4780 | 5360 | 6000 | 6570 | 7130 |
| 40 | 2510 | 2910 | 3300 | 3950 | 4620 | 5250 | 5950 | 6530 | 7210 | 7830 |
| 30 | 3040 | 3520 | 3990 | 4740 | 5600 | 6390 | 7140 | 7970 | 8730 | 9480 |
| 25 | 3440 | 3980 | 4520 | 5400 | 6350 | 7210 | 8100 | 9020 | 9890 | 10750 |
| 15 | 3970 | 4590 | 5200 | 6220 | 7300 | 8320 | 9330 | 10360 | 11390 | 12370 |
| 5 | 4510 | 5210 | 5920 | 7050 | 8320 | 9480 | 10630 | 11790 | 12960 | 14090 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.