

# FL 252

<b>TIRE SIZE</b>	<b>6.00 - 9</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	РОТОРНЫЕ ГРАБЛИ / СЕНОВОРОШИЛКА / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ВИЛОЧНЫЙ ПОГРУЗЧИК
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TT



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94006854	<b>PR</b>	10
<b>SW (IN)</b>	6.7		
<b>OD (IN)</b>	21.7		
<b>RIM REC</b>	4.00 E		

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>123</b>
<b>15 LOAD WHEEL</b>	3780
<b>15 STEER WHEEL</b>	2910
<b>5 OTHER VEHICLES</b>	3780
<b>15 OTHER VEHICLES</b>	2910
<b>STATIC SIDE LOADER</b>	4400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.