

AGRIMAX RT 855

| | |
|---------------------|---|
| TIRE SIZE | 320/85 R 32 |
| UM | US STANDARD |
| CONSTRUCTION | |
| MACHINERY | SPRAYER / VINEYARD HARVESTER / TRACTOR / HARVESTER / IMPLEMENTS |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 126 A8/B |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94021598 | RC (IN) | 160.7 |
| SW (IN) | 13.0 | RIM REC | W 11 |
| OD (IN) | 53.4 | RIM ALT | W 9 ; W 10 |
| SLR (IN) | 24.4 | ECE | E4-106R-000758 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 |
|-----------|------|------|------|------|------|------|
| 30 | 2060 | 2400 | 2740 | 3080 | 3420 | 3750 |
| 25 | 2060 | 2400 | 2740 | 3080 | 3420 | 3750 |
| 20 | 2220 | 2570 | 2930 | 3300 | 3660 | 4010 |
| 5 LT | 2770 | 3220 | 3670 | 4120 | 4570 | 5030 |
| 5 HT | 2220 | 2570 | 2930 | 3300 | 3660 | 4010 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.