

# AW 705

|                           |  |
|---------------------------|--|
| <b>TIRE SIZE</b>          | 15.0/55 - 17   |
| <b>UM</b>                 | IS STANDARD  |
| <b>CONSTRUCTION</b>       | ❖ BIAS   |
| <b>MACHINERY</b>          | ENFARDADEIRA DE FENO /<br>IMPLEMENTOS AGRÍCOLAS /<br>REBOQUE / CEIFEIRA / IMPLEMENTOS<br>AGRÍCOLAS |
| <b>VERSÃO</b>             | STANDARD   |
| <b>TIRE TYPE</b>          | TL   |
| <b>LI/SS FREE ROLLING</b> | 134 A8   |



## DIMENSÕES IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 381  | <b>RIM REC</b> | 13.00          |
| <b>OD (MM)</b>  | 850  | <b>RIM ALT</b> | 13; W 13       |
| <b>SLR (MM)</b> | 391  | <b>ECE</b>     | E4-106R-001546 |
| <b>RC (MM)</b>  | 2575 | <b>PR</b>      | 10             |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>2.60</b> |
|-------------------|-------------|
| 10 FR             | 2970        |
| 25 FR             | 2525        |
| 30 FR             | 2375        |
| 40 FR             | 2120        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.