

FLOTATION TR 675

TIRE SIZE	500/60 - 22.5
UM	IS STANDARD
CONSTRUCTION	❖ BIAS
MACHINERY	MAȘINI DE IMPLEMENTARE / REMORCĂ / MAȘINI DE IMPLEMENTARE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	151 A8/ 148 B
LI/SS FREE ROLLING	163 A8/159 B



DIMENSIUNI IS STANDARD

SW (MM)	515	RIM REC	AG 16.00
OD (MM)	1181	RIM ALT	15.00; 17.00
SLR (MM)	542	ECE	E11-106R-003605
RC (MM)	3604	PR	16

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.80	3.00	3.20
10 FR	6315	6575	6825
20 FR	5685	5915	6145
30 FR	5050	5260	5460
40 FR	4510	4695	4875
50 FR	4060	4225	4375
10 DW	4465	4650	4830
20 DW	4020	4185	4345
30 DW	3575	3720	3865
40 DW	3190	3320	3450
50 DW	2870	2990	3150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.