


# AGRIMAXFACTOR

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>620/70 R 46</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRACTOR  |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 162 D ; 165 A8   |



## DIMENSIUNI IS STANDARD

|                 |      |                 |                  |
|-----------------|------|-----------------|------------------|
| <b>SW (MM)</b>  | 625  | <b>RIM REC</b>  | DW 20 B          |
| <b>OD (MM)</b>  | 2036 | <b>ECE</b>      | E11-106R-0010339 |
| <b>SLR (MM)</b> | 913  | <b>SRI</b>      | 975              |
| <b>RC (MM)</b>  | 6075 | <b>TRA CODE</b> | R1W              |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6  | 0.8  | 1    | 1.2  | 1.4  | 1.6  |
|------------|------|------|------|------|------|------|
| 65         | 2615 | 3040 | 3470 | 3895 | 4325 | 4750 |
| 50         | 2745 | 3195 | 3645 | 4095 | 4545 | 4990 |
| 40         | 2865 | 3335 | 3800 | 4270 | 4740 | 5205 |
| 30         | 3010 | 3500 | 3990 | 4485 | 4975 | 5465 |
| 10 LT      | 3505 | 4075 | 4650 | 5220 | 5795 | 6365 |
| 10HT       | 3010 | 3500 | 3990 | 4485 | 4975 | 5465 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.