


# AGRIMAX RT 945

<b>TIRE SIZE</b>	<b>320/90 R 42</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZATOR / TRACTOR / MAŞINI DE IMPLEMENTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	139 A8/B



## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94038664	<b>RC (IN)</b>	194.6
<b>SW (IN)</b>	12.6	<b>RIM REC</b>	W 10
<b>OD (IN)</b>	64.7	<b>RIM ALT</b>	W 9; W 11
<b>SLR (IN)</b>	29.9	<b>ECE</b>	E4-106R-000783

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41
30	2900	3760	4610	4980	5360	-
25	2900	3760	4610	4980	5360	-
20	3110	4020	4950	5350	5740	-
5	4270	5220	6350	7400	7800	8040

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.